

Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name : Aseptopol EL 75

Product code : 114813E

Use of the : Manual Warewashing Detergent

Substance/Mixture

Substance type: : Mixture

For professional users only.

Product dilution information : 0.5 % - 2.0 %

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Dishwash product. Manual process

General purpose cleaner. Manual process Biocide. Spray and rinse manual process

Recommended restrictions

on use

: Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Ltd.

PO Box 11; Winnington Avenue

Northwich, Cheshire, United Kingdom CW8 4DX

+353 (0)1 276 3500 ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone : +353766805288

number +32-(0)3-575-5555 Trans-European

Poison Information Centre : For medical professionals only:

telephone number +353 (0)1 837 9964 (8am-10pm)

Date of Compilation/Revision : 26.10.2018

Version : 3.1

Section: 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Product AS SOLD

Serious eye damage, Category 1 H318
Chronic aquatic toxicity, Category 1 H410
The classification of this product is based on toxicological assessment.

114813E 1 / 19

Product AT USE DILUTION

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Product AS SOLD

Hazard pictograms





Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.

H410 Very toxic to aquatic life with long lasting

effects.

Precautionary Statements : Prevention:

P273 Avoid release to the environment. P280e Wear eye protection/face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water

for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

Alcohols, C9-11, ethoxylated

N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine

Didecyl Dimethyl Ammonium Chloride

Product AT USE DILUTION

Not a hazardous substance or mixture.

2.3 Other hazards

Product AS SOLD

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Product AS SOLD Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration: [%]
Alcohols, C9-11, ethoxylated	68439-46-3 01-2119979533-26	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318	>= 10 - < 20
1-Propanaminium, 3- amino-N-(carboxymethyl)- N,N-dimethyl-, N-coco	61789-40-0 263-058-8 01-2119489410-39	Serious eye damage Category 1; H318	>= 2.5 - < 3

114813E 2 / 19

acyl derivs., hydroxides, inner salts					
N-(3-aminopropyl)-N- dodecylpropane-1,3- diamine	2372-82-9 219-145-8 01-2119980592-29	Acute toxicity Category 3; H301 Skin corrosion Category 1A; H314 Serious eye damage Category 1; H318 Specific target organ toxicity - repeated exposure Category 2; H373 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410	>= 1 - < 2.5		
Didecyl Dimethyl Ammonium Chloride	7173-51-5 230-525-2 01-2119945987-15	Acute toxicity Category 4; H302 Skin corrosion Category 1B; H314 Chronic aquatic toxicity Category 2; H411 Acute aquatic toxicity Category 1; H400	>= 1 - < 2.5		
Substances with a workplace exposure limit :					
ethanol	64-17-5 200-578-6 01-2119457610-43	Flammable liquids Category 2; H225	>= 1 - < 2.5		
Isopropyl Alcohol	67-63-0 200-661-7 01-2119457558-25	Flammable liquids Category 2; H225 Eye irritation Category 2; H319 Specific target organ toxicity - single exposure Category 3; H336	>= 0.5 - < 1		

Product AT USE DILUTION Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration: [%]
N-(3-aminopropyl)-N- dodecylpropane-1,3- diamine	2372-82-9 219-145-8 01-2119980592-29	Acute toxicityCategory 3; H301 Skin corrosionCategory 1A; H314 Serious eye damageCategory 1; H318 Specific target organ toxicity - repeated exposureCategory 2; H373 Acute aquatic toxicityCategory 1; H400 Chronic aquatic toxicityCategory 1; H410	< 0.1
Didecyl Dimethyl Ammonium Chloride	7173-51-5 230-525-2 01-2119945987-15	Acute toxicityCategory 4; H302 Skin corrosionCategory 1B; H314 Chronic aquatic toxicityCategory 2; H411 Acute aquatic toxicityCategory 1; H400	< 0.1

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES

4.1 Description of first aid measures

Product AS SOLD

In case of eye contact

: Rinse immediately with plenty of water, also under the eyelids, for

at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

In case of skin contact : Rinse with plenty of water.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention

if symptoms occur.

114813E 3 / 19

Product AT USE DILUTION

In case of eye contact : Rinse with plenty of water.

In case of skin contact : Rinse with plenty of water.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

Product AS SOLD

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Fire Hazard

Keep away from heat and sources of ignition. Flash back possible over considerable distance.

Beware of vapours accumulating to form explosive concentrations.

Vapours can accumulate in low areas.

Hazardous combustion

products

: Depending on combustion properties, decomposition products

may include following materials:

Carbon oxides

nitrogen oxides (NOx) Sulphur oxides Oxides of phosphorus

5.3 Advice for firefighters

for firefighters

Special protective equipment : Use personal protective equipment.

Further information : Collect contaminated fire extinguishing water separately. This

> must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or

explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

114813E 4/19

Product AS SOLD

Advice for non-emergency personnel

: Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency

responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

Product AT USE DILUTION

Advice for non-emergency personnel

Advice for emergency

responders

: Refer to protective measures listed in sections 7 and 8.

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable

materials.

6.2 Environmental precautions

Product AS SOLD

Environmental precautions : Do not allow contact with soil, surface or ground water.

Product AT USE DILUTION

Environmental precautions : No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

Product AS SOLD

Methods for cleaning up

Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Methods for cleaning up

: Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information. For personal protection see section 8. See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

114813E 5/19

Product AS SOLD

Advice on safe handling : Do not get in eyes, on skin, or on clothing. Use only with adequate

ventilation. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Wash hands thoroughly

after handling. Do not breathe spray, vapour.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Remove and wash contaminated clothing before re-use.

Wash face, hands and any exposed skin thoroughly after

handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

Advice on safe handling : Wash hands after handling. For personal protection see section 8.

Hygiene measures : Wash hands before breaks and immediately after handling the

product.

7.2 Conditions for safe storage, including any incompatibilities

Product AS SOLD

Requirements for storage areas and containers

: Keep away from heat and sources of ignition. Keep away from oxidizing agents. Keep out of reach of children. Keep container

tightly closed. Store in suitable labeled containers.

Storage temperature : 0 °C to 40 °C

Product AT USE DILUTION

Requirements for storage areas and containers

: Keep out of reach of children. Keep container tightly closed. Store

in suitable labeled containers.

7.3 Specific end uses

Product AS SOLD

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Product AS SOLD

Occupational Exposure Limits

Components	CAS-No.		ue type (Form xposure)	Control parameters	Basis
ethanol	64-17-5	OE	_V - 15 min EL)	1,000 ppm	IR_OEL
Isopropyl Alcohol	67-63-0	OE (TV	_V - 8 hrs /A)	200 ppm	IR_OEL
Further information	Sk	Sk Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
		OE (ST	_V - 15 min EL)	400 ppm	IR_OEL
Further information	Sk			capacity to penetrate intact ski sorbed into the body	n when they come

DNEL

Isopropyl Alcohol	:	End Use: Workers
		Exposure routes: Dermal

114813E 6 / 19

Potential health effects: Long-term systemic effects

Value: 888 mg/cm2

End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 500 mg/m3

End Use: Consumers Exposure routes: Dermal

Potential health effects: Long-term systemic effects

Value: 319 mg/cm2

End Use: Consumers Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 89 mg/m3

End Use: Consumers
Exposure routes: Ingestion

Potential health effects: Long-term systemic effects

Value: 26 ppm

PNEC

Isopropyl Alcohol	:	Fresh water Value: 140.9 mg/l
		Marine water Value: 140.9 mg/l
		Intermittent use/release Value: 140.9 mg/l
		Fresh water Value: 552 mg/kg
		Marine sediment Value: 552 mg/kg
		Soil Value: 28 mg/kg
		Sewage treatment plant Value: 2251 mg/l
		Oral Value: 160 mg/kg

8.2 Exposure controls

Product AS SOLD Appropriate engineering controls

Engineering measures : Good general ventilation should be sufficient to control worker

exposure to airborne contaminants.

114813E 7 / 19

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Remove and wash contaminated clothing before re-use.

Wash face, hands and any exposed skin thoroughly after

handling. Provide suitable facilities for quick drenching or flushing

of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles

Face-shield

Hand protection (EN 374) : No special protective equipment required.

Skin and body protection

(EN 14605)

: No special protective equipment required.

Respiratory protection (EN

143, 14387)

: None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified

respiratory protection equipment meeting EU

requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods

or procedures of work organization.

Product AT USE DILUTION Appropriate engineering controls

Engineering measures : Good general ventilation should be sufficient to control worker

exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands before breaks and immediately after handling the

product.

Eye/face protection (EN

166)

: No special protective equipment required.

Hand protection (EN 374) : No special protective equipment required.

Skin and body protection

(EN 14605)

: No special protective equipment required.

Respiratory protection (EN

143, 14387)

: None required if airborne concentrations are maintained below the

exposure limit listed in Exposure Limit Information. Use certified

respiratory protection equipment meeting EU

requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods

or procedures of work organization.

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

114813E 8 / 19

9.1 Information on basic physical and chemical properties

Appearance : liquid liquid
Colour : clear, light green colourless
Odour : odourless odourless

Product AS SOLD

Product AT USE DILUTION

pH : 10.5 - 11.5, 100 % 8.8 - 9.4

Flash point : 60 °C, Does not sustain combustion.

Odour Threshold : Not applicable and/or not determined for the mixture

Melting point/freezing point : Not applicable and/or not determined for the mixture

Initial boiling point and : Not applicable and/or not determined for the mixture

boiling range

Evaporation rate : Not applicable and/or not determined for the mixture Flammability (solid, gas) : Not applicable and/or not determined for the mixture Upper explosion limit : Not applicable and/or not determined for the mixture Lower explosion limit : Not applicable and/or not determined for the mixture Vapour pressure : Not applicable and/or not determined for the mixture Relative vapour density : Not applicable and/or not determined for the mixture

Relative density : 0.99 - 1.03 Water solubility : soluble

Solubility in other solvents : Not applicable and/or not determined for the mixture Partition coefficient: n- : Not applicable and/or not determined for the mixture

Auto-ignition temperature : Not applicable and/or not determined for the mixture Thermal decomposition : Not applicable and/or not determined for the mixture

Viscosity, kinematic : 19.838 mm2/s (40 °C)

Explosive properties : Not applicable and/or not determined for the mixture Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

octanol/water

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

Product AS SOLD 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

114813E 9 / 19

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials:

Carbon oxides

nitrogen oxides (NOx)

Sulphur oxides

Oxides of phosphorus

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Product AS SOLD

exposure

Information on likely routes of : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg

Acute inhalation toxicity : There is no data available for this product.

Acute dermal toxicity : There is no data available for this product.

Skin corrosion/irritation : No skin irritation

Method: OECD Test Guideline 404

Test substance: Product

Serious eye damage/eye

irritation

: There is no data available for this product.

Respiratory or skin

sensitization

: There is no data available for this product.

Carcinogenicity : There is no data available for this product.

Reproductive effects : There is no data available for this product.

Germ cell mutagenicity : There is no data available for this product.

Teratogenicity : There is no data available for this product.

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

114813E 10/19

Components

Acute oral toxicity : Alcohols, C9-11, ethoxylated

LD50 rat: 1,400 mg/kg

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-

coco acyl derivs., hydroxides, inner salts

LD50 rat: 2,600 mg/kg

N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine

LD50 rat: 261 mg/kg

Didecyl Dimethyl Ammonium Chloride

LD50 rat: 1,150 mg/kg

ethanol

LD50 rat: 10,470 mg/kg

Isopropyl Alcohol LD50 rat: 5,840 mg/kg

Components

Acute inhalation toxicity : ethanol

4 h LC50 rat: 117 mg/l Test atmosphere: vapour

Isopropyl Alcohol 4 h LC50 rat: > 30 mg/l Test atmosphere: vapour

Components

Acute dermal toxicity : Alcohols, C9-11, ethoxylated

LD50 rat: > 5,000 mg/kg

Didecyl Dimethyl Ammonium Chloride

LD50 rabbit: 2,930 mg/kg

ethanol

LD50 rabbit: > 15,800 mg/kg

Isopropyl Alcohol

LD50 rabbit: 12,870 mg/kg

Potential Health Effects

Product AS SOLD

Eyes : Causes serious eye damage.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes : Health injuries are not known or expected under normal use.

114813E 11 / 19

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

Eve contact : Redness, Pain, Corrosion

Skin contact : No symptoms known or expected.

Ingestion : No symptoms known or expected.

Inhalation : No symptoms known or expected.

Product AT USE DILUTION

Eye contact : No symptoms known or expected.

Skin contact : No symptoms known or expected.

Ingestion : No symptoms known or expected.

Inhalation : No symptoms known or expected.

Section: 12. ECOLOGICAL INFORMATION

Product AS SOLD 12.1 Ecotoxicity

Environmental Effects : Very toxic to aquatic life with long lasting effects.

Product

Toxicity to fish Very toxic to aquatic life.:

Test substance: Similar Product

Toxicity to daphnia and other : no data available

aquatic invertebrates

: no data available Toxicity to algae

Toxicity to fish (Chronic

: Very toxic to aquatic life with long lasting effects.:

toxicity)

Test substance: Similar Product

Components

Toxicity to fish : Alcohols, C9-11, ethoxylated

96 h LC50 Fish: 8.5 mg/l

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-

coco acyl derivs., hydroxides, inner salts

96 h LC50 Fish: 2 mg/l

Didecyl Dimethyl Ammonium Chloride

96 h LC50 Fish: 1 mg/l

114813E 12/19

ethanol

96 h LC50 Pimephales promelas (fathead minnow): > 100 mg/l

Isopropyl Alcohol

96 h LC50 Pimephales promelas (fathead minnow): 9,640 mg/l

Components

aquatic invertebrates

Toxicity to daphnia and other : Alcohols, C9-11, ethoxylated

48 h EC50 Daphnia magna (Water flea): 5.3 mg/l

Isopropyl Alcohol

LC50 Daphnia magna (Water flea): > 10,000 mg/l

Components

Toxicity to algae : N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine

72 h EC50: 0.014 mg/l

12.2 Persistence and degradability

Product

Biodegradability : The surfactants contained in the product are biodegradable

according to the requirements of the detergent regulation

648/2004/EC

Components

Biodegradability : Alcohols, C9-11, ethoxylated

Result: Readily biodegradable.

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-

coco acyl derivs., hydroxides, inner salts

Result: Readily biodegradable.

N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine

Result: Readily biodegradable.

Didecyl Dimethyl Ammonium Chloride Result: Eliminated from aquatic environment

ethanol

Result: Readily biodegradable.

Isopropyl Alcohol

Result: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be

114813E 13/19

either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product AS SOLD

Product : The product should not be allowed to enter drains, water courses

or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an

approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken

to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local,

state, and federal regulations.

Guidance for Waste Code

selection

: Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC)

and local regulations.

Product AT USE DILUTION

Product : Diluted product can be flushed to sanitary sewer.

Contaminated packaging : Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number : 3082

14.2 UN proper shipping : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

name N.O.S.

(Alkylamine(s), Alkyl ammonium chloride)

14.3 Transport hazard

class(es)

14.4 Packing group : III

114813E 14 / 19

14.5 Environmental hazards : Yes

14.6 Special precautions for

user

: None

Air transport (IATA)

14.1 UN number : 3082

14.2 UN proper shipping : Environmentally hazardous substance, liquid, n.o.s.

name

(Alkylamine(s), Alkyl ammonium chloride)

14.3 Transport hazard : 9

class(es)

14.4 Packing group : III 14.5 Environmental hazards : Yes

14.6 Special precautions for : None

user

Sea transport (IMDG/IMO)

14.1 UN number : 3082

14.2 UN proper shipping : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

name N.O.S.

(Alkylamine(s), Alkyl ammonium chloride)

14.3 Transport hazard : 9

class(es)

14.4 Packing group : III 14.5 Environmental hazards : Yes

14.6 Special precautions for

user

: None

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC

Code

: Not applicable.

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents : 5 % or over but less than 15 %: Non-ionic surfactants

Regulation EC 648/2004 less than 5 %: Amphoteric surfactants

Contains: Disinfectants

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : Safety, Health and Welfare at Work Act, 2005

European Communities (Classification, Packaging, Labelling and Notification of Dangerous Preparations) Regulations 1995. (S.I.

272 of 1995) as amended

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

114813E 15 / 19

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Serious eye damage 1, H318	Calculation method
Chronic aquatic toxicity 1, H410	Calculation method

Full text of H-Statements

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM -American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL -Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number -European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx – Concentration associated with x% growth rate response; GHS - Globally Harmonized System: GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 – Lethal Concentration to 50 % of a test population; LD50 – Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL – International Convention for the Prevention of Pollution from Ships; n.o.s. – Not Otherwise Specified; NO(A)EC No Observed (Adverse) Effect Concentration; NO(A)EL – No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR – (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID – Regulations concerning the International Carriage of Dangerous Goods by Rail: SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB -Very Persistent and Very Bioaccumulative

114813E 16 / 19

Further information

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: Biocide. Spray and rinse manual process

Exposure Scenario: Dishwash product. Manual process

Life Cycle Stage : Widespread use by professional workers

: PC35 Product category Washing and cleaning products (including solvent based

products)

Contributing scenario controlling environmental exposure for:

Environmental release

category

: ERC8a

Wide dispersive indoor use of processing aids in open

systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment

Plant

: Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Roller application or brushing Process category PROC10

Exposure duration 480 min

Operational conditions and

risk management measures

Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection No

Respiratory Protection No

114813E 17 / 19 : Indoor

Aseptopol EL 75

Contributing scenario controlling worker exposure for:

PROC8a Process category Transfer of substance or preparation (charging/

discharging) from/ to vessels/ large containers at non-

dedicated facilities

Exposure duration 60 min

Operational conditions and

risk management measures

Local Exhaust Ventilation is not required

General ventilation 1 Ventilation rate per hour

Skin Protection Yes: See Section 8

Respiratory Protection No

Exposure Scenario: General purpose cleaner. Manual process

Widespread use by professional workers Life Cycle Stage

Product category PC35 Washing and cleaning products (including solvent based

products)

Contributing scenario controlling environmental exposure for:

Environmental release ERC8a Wide dispersive indoor use of processing aids in open

category

systems

Daily amount per site 7.5 kg

Type of Sewage Treatment

Plant

Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category PROC10 Roller application or brushing

Exposure duration 480 min

Operational conditions and

risk management measures

Indoor

Local Exhaust Ventilation is not required

1 General ventilation Ventilation rate per hour

Skin Protection No

Respiratory Protection No

Contributing scenario controlling worker exposure for:

Process category PROC8a Transfer of substance or preparation (charging/

discharging) from/ to vessels/ large containers at non-

114813E 18 / 19 : Indoor

Aseptopol EL 75

dedicated facilities

Exposure duration 60 min

Operational conditions and

risk management measures

Local Exhaust Ventilation is not required

1 General ventilation Ventilation rate per hour

Skin Protection : Yes: See Section 8

Respiratory Protection

114813E 19/19