

Product RELOAD No.11 - BACTI-VIR  
 Revision date 24 June 2020  
 Revision 2



## Safety Data Sheet (SDS)

### Section 1: Identification of the substance/preparation and of the company/undertaking

#### 1.1 Product identifier

Product name RELOAD No.11 - BACTI-VIR  
 Product no. REAQUABACTIVIR  
 Synonyms, Trade names No information available.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaning and disinfecting agent.  
 Uses advised against Any other purpose.

#### 1.3 Details of the supplier of the safety data sheet

Supplier Kitchenmaster NI Ltd  
 11 Comber Road  
 Belfast  
 BT8 8AN  
 United Kingdom  
 Tel: 028 9081477 02890812881  
 sales@kitchenmaster-ni.com  
 Contact person

#### 1.4 Emergency telephone number

Emergency telephone Emergency Telephone Number: 028 9081 4777 08:30 - 17:00 Monday to Thursday 08:30 - 16:30 Friday

### Section 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification (EC 1272/2008)  
 Physical and chemical hazards Not classified  
 Human health Skin Corr. 1B - H314, Eye Dam. 1 - H318  
 Environment Aquatic Acute 1 - H400, Aquatic Chronic 2 - H411

#### 2.2 Label elements

Contains Alcohols, C12-13, ethoxylated  
 disodium metasilicate  
 Benzyl-C12-18-alkyldimethylammonium chlorides (mixture)

Label in accordance with (EC) no.  
 1272/2008



Signal word Danger

Hazard statements H314 Causes severe skin burns and eye damage.  
 H400 Very toxic to aquatic life.  
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements Prevention  
 P260 Do not breathe dust/fume/ gas/mist/vapours/spray.  
 P280 Wear protective gloves/ protective clothing/eye protection/face protection.

**Response**

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

**2.3 Other hazards**

None known.

**Section 3: Composition/identification of ingredients****3.1 Substance**

Not applicable.

**3.2 Mixtures**

Name	Product identifier	Reg. EU 1272/2008	%
Dipropylene Glycol Monomethyl Ether	CAS-No.: 252-104-2 EC No.: 34590-94-8	Not classified	5-15%
Alcohol, C12-13 - Branched and Linear, Ethoxylated (>5 -<15 EO)	CAS-No.: 160901-19-9 EC No.: 931-954-4	Eye Dam. 1 - H318, Acute Tox 4 - H302, Aquatic Chronic 3 - H412	1-10%
Tetrasodium salt of Hydroxy ethylidene-1,1diphosphonic acid	CAS-No.: 3794-83-0 EC No.: 223-267-7	Skin Corr, 1A - H314	1-10%
disodium metasilicate	CAS-No.: 6834-92-0 EC No.: 229-912-9	Skin Corr. 1B - H314, STOT SE 3 - H335	1-10%
Alkyl (C12-C14) ethylbenzylammonium chloride (ADEBAC (C12-C14))	CAS-No.: 85409-23-0 EC No.: 287-090-7	Acute Tox 4 - H302, Skin Corr. 1B - H314, Aquatic Acute 1 - H400, Aquatic Chronic 1 - H410	1-10%
Alkyl (C12-18) dimethylbenzyl ammonium chloride (ADBAC (C12-18))	CAS-No.: 68391-01-5 EC No.: 269-919-4	Acute Tox 4 - H302, Skin Corr. 1B - H314, Aquatic Acute 1 - H400, Aquatic Chronic 1 - H410	1-10%

The full text for all hazard statements are displayed in section 16.

**Composition comments**

The data shown are in accordance with the latest EC Directives.

**Section 4: First aid measures****4.1 Description of first aid measures****General information**

Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if symptoms persist, always call a doctor. Seek medical attention for all burns and eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during rescue.

**Inhalation**

Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

**Ingestion**

If this product is ingested, remove victim immediately from source of exposure. Rinse mouth thoroughly. Do not induce vomiting. Provide fresh air, warmth and rest. Get medical attention. Never give anything by mouth to an unconscious person.

**Skin contact**

Remove victim immediately from source of exposure. Remove contaminated clothing, shoes and jewelry and wash before reuse. Wash the skin immediately with water. Obtain medical attention if irritation persists or if blistering occurs.

**Eye contact**

Do not rub eye. If this product contacts the eyes, gently flush eyes with water for at least fifteen (15) minutes, lifting the upper and lower eyelids occasionally. Remove contact lenses if present and easy to do so. Avoid contaminating unaffected eye. Seek medical attention.

**4.2 Most important symptoms and effects, both acute and delayed****General information**

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

**Inhalation**

Inhalation of mist or vapor may cause respiratory tract irritation.

**Ingestion**

May cause stomach pain or vomiting. May cause chemical burns in mouth and throat.

**Skin contact**

May cause serious chemical burns to the skin.

Eye contact	Causes serious eye damage. Extreme irritation of eyes and mucous membranes, including burning and tearing.
-------------	--

#### **4.3 Indication of any immediate medical attention and special treatment needed**

Notes to the physician	Treat symptomatically.
------------------------	------------------------

---

### **Section 5: Fire-fighting measures**

---

#### **5.1 Extinguishing media**

Extinguishing media	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media	None noted.

#### **5.2 Special hazards arising from the substance or mixture**

Hazardous combustion products	When heated, toxic and corrosive vapours/gases may be formed. During fire, toxic gases (CO, CO <sub>2</sub> ) are formed.
Unusual fire & explosion hazards	No unusual fire or explosion hazards noted.
Specific hazards	Fire creates: Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ). Do not allow run-off from fire fighting to enter drains or water courses.

#### **5.3 Advice for firefighters**

Special fire fighting procedures	If possible, fight fire from protected position. Avoid breathing fire vapours. Ventilate closed spaces before entering them. Containers close to fire should be removed immediately or cooled with water if safe to do so.
Protective equipment for firefighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

---

### **Section 6: Accidental release measures**

---

#### **6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation. Eliminate all sources of ignition. Avoid inhalation of vapours and contact with skin and eyes. In case of inadequate ventilation, use respiratory protection. Do not touch or walk through spilled material. If necessary evacuate surrounding areas.
For emergency responders	Follow safe handling advice and personal protective equipment recommendations for normal use of product.

#### **6.2 Environmental precautions**

Environmental precautions	Do not discharge onto the ground or into water courses. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.
---------------------------	--

#### **6.3 Methods and material for containment and cleaning up**

Spill clean up methods	Stop leak if possible without risk. Eliminate all sources of ignition. Ventilate and evacuate the area. DO NOT touch spilled material! When dealing with a spillage, wear necessary protective equipment. Absorb spillage with non-combustible, inert absorbent material. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container. Wash thoroughly after dealing with a spillage.
------------------------	--

#### **6.4 Reference to other sections**

Reference to other sections	See section 1 for emergency contact. For personal protection, see section 8. For waste disposal, see section 13.
-----------------------------	--

---

### **Section 7: Handling and storage**

---

**7.1 Precautions for safe handling**

Handling	Read and follow manufacturer's recommendations. Use proper personal protection when handling (refer to Section 8). Do not handle broken packages without protective equipment. Do not use contact lenses. Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Do not eat, drink or smoke when using the product. Wash thoroughly after handling.
----------	---

**7.2 Conditions for safe storage, including any incompatibilities**

Storage precautions	Keep upright, locked up and out of reach of children. Keep the product in its original container. Store in cool dry areas away from direct sunlight or sources of ignition.
Storage class	Corrosive storage.

**7.3 Specific end use(s)**

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
Usage description	Use only according to directions. Replace and tighten cap after use.

**Section 8: Exposure controls/Personal protection****8.1 Control parameters**

Component	STD	TWA (8 Hrs)	STEL (15mins)	Notes
No components listed in EH40 or OEL				

Ingredient comments	WEL - Workplace Exposure Limits - EH40/2005 Workplace exposure limits. OEL - Occupational Exposure Limit - Ireland, Occupational Exposure Limits 2016.
---------------------	---

**8.2 Exposure Controls****Protective equipment**

Engineering measures	Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.
Respiratory equipment	If ventilation is inadequate, suitable respiratory protection must be worn. EN 136/140/145/143/149. The specific respirator selected must be based on contamination levels found in the work place. Where risk assessment shows air-purifying respirators are appropriate a full face respirator conforming to EN143 should be used, and suitable respirator cartridges as a backup to engineering controls. Recommended: Respirator with combination filter for vapour/particulate (EN 141). Consult manufacturer for specific advice.
Hand protection	Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374) is recommended. (EU Directive 89/686/EEC). Gloves must be inspected prior to use. Suggested material: Butyl-rubber. Breakthrough time: >480 minutes. Minimum layer thickness: 0.33 mm. Consult manufacturer for advice. Selection of the glove material depends on consideration of the penetration times, rates of diffusion and degradation, and concentration specific to the workplace. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.
Eye protection	Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU).
Other protection	Wear appropriate clothing to prevent skin contact. The selected clothing must satisfy the European norm standard EN 943. Personal protective equipment for the body should be

Hygiene measures	selected based on the task being performed and the risks involved and should be approved by a specialist before handing this product. Work clothing worn by personnel shall be laundered regularly. After contact with the product, all parts of the body that have been soiled must be washed.
Process conditions	Observe normal hygiene standards. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash hands after use. Ensure that eye flushing systems and safety showers are located close by in the work place.

---

## Section 9: Physical and chemical properties

---

### 9.1 Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Dark Purple.
Odour	No information available.
Odour threshold - lower	No information available.
Odour threshold - upper	No information available.
pH-Value, Conc. Solution	13-14
pH-Value, Diluted solution	No information available.
Melting point	No information available.
Initial boiling point and boiling range	No information available.
Flash point	No information available.
Evaporation rate	No information available.
Flammability state	No information available.
Flammability limit - lower(%)	No information available.
Flammability limit - upper(%)	No information available.
Vapour pressure	No information available.
Vapour density (air=1)	No information available.
Relative density	1.06 - 1.07g/cm <sup>3</sup> @ 20.00 °C
Bulk density	No information available.
Solubility	Soluble in water.
Decomposition temperature	Not applicable.
Partition coefficient; n-Octanol/Water	No information available.
Auto ignition temperature ( °C)	No information available.
Viscosity	No information available.
Explosive properties	Not classified as explosive.
Oxidising properties	No information available.

### 9.2 Other information

Molecular weight	No information available.
Volatile organic compound	No information available.
Other information	None noted.

**Section 10: Stability and reactivity****10.1 Reactivity**

**Reactivity** Reactions may occur with strong oxidizing materials and strong acids.

**10.2 Chemical stability**

**Stability** Stable under normal temperature conditions and recommended use.

**10.3 Possibility of hazardous reactions**

**Hazardous reactions** Avoid strong oxidizers. Reacts with acids.  
**Hazardous polymerisation** Will not polymerise.  
**Polymerisation description** Not applicable.

**10.4 Conditions to Avoid**

**Conditions to avoid** Heat, sparks, open flames, temperature extremes and direct sunlight. Avoid storing in large quantities or for long periods of time.

**10.5 Incompatible materials**

**Materials to avoid** Do not mix with other chemicals unless listed on directions. Avoid strong oxidising agents, bases, strong acids. Avoid contact with Aluminium, Zinc, Lead, Tin and alloys of these metals

**10.6 Hazardous decomposition products**

**Hazardous decomposition products** Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

**Section 11: Toxicological information****11.1 Information on toxicological effects**

**Toxicological information** No toxicological information for the overall finished product.

**Acute toxicity (Oral LD50)** Alcohols, C12 -13, ethoxylated (CAS 160901-19-9): > 5000 mg/kg, Rat. REACH dossier information. BENZALKONIUM CHLORIDE (CAS 68391-01-5): 150 mg/kg, Mouse. DISODIUM METASILICATE (CAS 6834-92-0): 994 mg/kg, Rat. REACH dossier information.

**Acute toxicity (Dermal LD50)** Alcohols, C12 -15, ethoxylated (CAS 68131-39-5): > 2000 mg/kg, Rat. REACH dossier information. BENZALKONIUM CHLORIDE (CAS 68391-01-5): 1420 mg/kg, Rat. DISODIUM METASILICATE (CAS 6834-92-0): > 3000 mg/kg, Rat. REACH dossier information.

**Acute toxicity (Inhalation LD50)** Alcohols, C12 -15, ethoxylated (CAS 68131-39-5): > 1.6 mg/l, (dust/mist) Rat - 4 hours. REACH dossier information. DISODIUM METASILICATE (CAS 6834-92-0): > 2.06 mg/l, (vapours) Rat. REACH dossier information.

**Serious eye damage/irritation** Causes severe eye damage.

**Skin corrosion/irritation** No information available.

**Respiratory sensitisation** No information available.  
**Skin sensitisation** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** No information available.

**Specific target organ toxicity - Single exposure:**  
**STOT - Single exposure** No information available.  
**Specific target organ toxicity - Repeated exposure:**  
**STOT - Repeated exposure** No information available.

**Inhalation** Inhalation of mist or vapor may cause respiratory tract irritation.  
**Ingestion** May cause stomach pain or vomiting. May cause chemical burns in mouth and throat.  
**Skin contact** May cause serious chemical burns to the skin.  
**Eye contact** Causes serious eye damage. Extreme irritation of eyes and mucous membranes, including burning and tearing.

**Waste management** When handling waste, consideration should be made to the safety precautions applying to

	handling of the product.
Routes of entry	No information available.
Target organs	Eyes, skin, digestive system, respiratory system.
Aspiration hazards:	No information available.
Reproductive toxicity:	No information available.

---

## Section 12: Ecological information

---

### 12.1 Toxicity

Acute toxicity - Fish	Alcohols, C12 -13, ethoxylated (CAS 160901-19-9) LC50: (96 hours) 0.59 mg/l, Pleuronectes platessa. REACH dossier information. BENZALKONIUM CHLORIDE (CAS 68391-01-5): LC50 96 hours 0.31 mg/l Lepomis macrochirus (Bluegill.) DISODIUM METASILICATE (CAS 6834-92-0) LC50: (96 hours) 210 mg/l, Brachydanio rerio (Zebra Fish.) REACH dossier information.
Acute toxicity - Aquatic invertebrates	Alcohols, C12 -13, ethoxylated (CAS 160901-19-9) EC50: (48 hours) 0.14 mg/l, Daphnia magna. REACH dossier information. DISODIUM METASILICATE (CAS 6834-92-0) EC50: (48 hours) 7.8 pH, Daphnia magna. REACH dossier information.
Acute toxicity - Aquatic plants	Alcohols, C12 -13, ethoxylated (CAS 160901-19-9) EC50: (72 hours) 0.75 mg/l, Selenastrum capricornutum. REACH dossier information. DISODIUM METASILICATE (CAS 6834-92-0) EC50: (72 hours) 207 mg/l, Desmodemus subspicatus. REACH dossier information.
Acute toxicity - Microorganisms	No information available.
Chronic toxicity - Fish	No information available.
Chronic toxicity - Aquatic invertebrates	No information available.
Chronic toxicity - Aquatic plants	No information available.
Chronic toxicity - Microorganisms	No information available.
Ecotoxicity	Very toxic to aquatic life with long lasting effects.
Eco toxicological information	No ecological toxicity available on the overall finished product.

### 12.2 Persistence and degradability

Degradability	All surfactants contained in this product are biodegradable according to the requirements of detergent regulation 648/2004/EC.
Biological oxygen demand	No information available.
Chemical oxygen demand	No information available.

### 12.3 Bioaccumulative potential

Bioaccumulative potential	No data available on bioaccumulation.
Bioaccumulation factor	No information available.
Partition coefficient; n-Octanol/Water	No information available.

### 12.4 Mobility in soil

Mobility	Soluble in water.
----------	-------------------

### 12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment None of the raw materials listed are classified as PBT / vPvB substances.

### 12.6 Other adverse effects

Other adverse effects	None known.
-----------------------	-------------

---

## Section 13: Disposal considerations

---

Waste management	When handling waste, consideration should be made to the safety precautions applying to handling of the product.
------------------	--

**13.1 Waste treatment methods**

Disposal methods	Dispose of waste and residues in accordance with local authority requirements. For waste disposal, use a licensed industrial waste disposal agent.
------------------	--

**Section 14: Transport information****14.1 UN number**

UN no. (ADR)	UN1760
UN no. (IMDG)	UN1760
UN no. (IATA)	UN1760

**14.2 UN proper shipping name**

ADR proper shipping name	CORROSIVE LIQUID, N.O.S. (disodium metasilicate + Benzyl-C12--14-alkyldimethylammonium chlorides)
IMDG proper shipping name	CORROSIVE LIQUID, N.O.S. (disodium metasilicate + Benzyl-C12--14-alkyldimethylammonium chlorides)
IATA proper shipping name	CORROSIVE LIQUID N.O.S. (disodium metasilicate + Benzyl-C12--4-alkyldimethylammonium chlorides)

**14.3 Transport hazard class(es)**

ADR class	8
IMDG class	8
IATA class	8

Transport labels

**14.4 Packing group**

ADR/RID/ADN packing group	III
IMDG packing group	III
IATA packing group	III

**14.5 Environmental hazards**

ADR	Yes
IMDG	Yes
IATA	Yes

**14.6 Special precautions for user**

EMS	F-A, S-B
Emergency action code	A3
Hazard no. (ADR)	80
Tunnel restriction code	(E)

**14.7 Transport in bulk according to annex II of MARPOL73/78 and the IBC code****Section 15: Regulatory information****15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture**

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 453/2010 of 20th May 2010 amending regulation (EC) No 1907/2006.
Approved code of practice	Workplace Exposure Limits Guidance Note EH40/2005.  2016 Code of Practice for the Chemical Agents Regulations in accordance with section 60 of



the Safety, Health and Welfare at Work Act 2005 (No. 10 of 2005).

**Chemical safety assessment**

No chemical safety assessment has been carried out.

---

**Section 16: Other information**

---

<b>General information</b>	This Safety Data Sheet is in accordance with Reach Regulation (EC) No 453/2010.
<b>Revision comments</b>	Modifications to section 3.
<b>Revision date</b>	24 June 2020
<b>Revision</b>	2
<b>Safety data sheet status</b>	Approved.

**Hazard statements in full**

<b>H302</b>	Harmful if swallowed.
<b>H318</b>	Causes serious eye damage.
<b>H400</b>	Very toxic to aquatic life.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H335</b>	May cause respiratory irritation.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.

**Disclaimer**

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.